



(51) International patent classification⁷:
F01P 7/16

F02B 29/04,

(72) Inventors; and

(75) Inventors/Applicants (US only): **HOLZBAUR, Thomas** [DE/DE]; Brunnenwiesenstrasse 44B, 70619 Stuttgart (DE). **MÜLLER, Rolf** [DE/DE]; Heinrich-Heine-Strasse 5, 71642 Ludwigsburg (DE). **PANTOW, Eberhard** [DE/DE]; Ellen-Key-Weg 8, 71696 Möglingen (DE). **PARMENTIER, Sarah** [FR/DE]; Schulstrasse 21, 70839 Gerlingen (DE). **WILLERS, Eike** [DE/DE]; Kräherstrasse 2, 70469 Stuttgart (DE).

(21) International application number: PCT/EP2004/014249

(22) International filing date: 15 December 2004 (15.12.2004)

(25) Language of filing: German

(26) Language of publication: German

(30) Data relating to the priority:
103 60 400.6 19 December 2003 (19.12.2003) DE

(74) Joint Representative: **BEHR GMBH & CO. KG**; Intellectual Property, G-IP, Mauserstrasse 3, 70469 Stuttgart (DE).

(71) Applicant (for all designated States except US): **BEHR GMBH & CO. KG** [DE/DE]; Mauserstrasse 3, 70469 Stuttgart (DE). **BEHR THERMOT-TRONIK GMBH** [DE/DE]; Enzstrasse 25, 70806 Kornwestheim (DE).


(81) Designated states (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DK, DM, DZ, EC,

[continued on next page]

As printed

(54) Title: CIRCUIT ARRANGEMENT FOR THE COOLING OF CHARGE AIR AND METHOD FOR OPERATION OF SUCH A CIRCUIT ARRANGEMENT

(54) Bezeichnung: KREISLAUFANORDNUNG ZUR KÜHLUNG VON LADELUFT UND VERFAHREN ZUM BETREIBEN EINER DERARTIGEN KREISLAUFANORDNUNG



(57) Abstract: The invention relates to a circuit arrangement (K), with a low-temperature coolant circuit (1) for the cooling of charge air on a motor vehicle with a charging device, comprising a charge air/coolant cooler (2). A temperature sensor (4) is provided at the exit of the coolant from the charge air/coolant cooler (2), or directly thereafter, for the measurement of the coolant exit temperature. The invention further relates to a method for operation of such a circuit arrangement (K).

[continued on next page]

EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for the following designation*
US

(84) Designated states (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF,

Published:

— *With International Search Report.*

For an explanation of the two-letter codes and the other abbreviations, reference is made to the explanations ("Guidance Notes on Codes and Abbreviations") at the beginning of each regular edition of the PCT Gazette.

(57) Zusammenfassung: Die Erfindung betrifft eine Kreislaufanordnung (K) mit einem Niedertemperatur-Kühlmittelkreislauf (1) zur Kühlung von Ladeluft bei einem Kraftfahrzeug mit einem Aufladegerät mit einem Ladeluft/Kühlmittel-Kühler (2), wobei ein Temperatur-Sensor (4) am Kühlmittelaustritt des Ladeluft/Kühlmittel-Kühlers (2) oder kurz danach zur Messung der Kühlmittelaustritts Temperatur vorgesehen ist, sowie ein Verfahren zum Betreiben einer derartigen Kreislaufanordnung (K).